

Functional programming in R (R'18)

TD 3: Control and Data flow

Exercise 1 What does the following expressions evaluate to, why/how, and what are their side effects (such as variable assignments)

1. `{y ← {x ← 2; y ← x-1}; y ← x+y}`
2. `{z ← y ← x ← 1; {y ← z + 1} + 3} + 2`
3. `{x ← 1; for (i in 1:3) {x ← x+i}}`
4. `{i ← 1; repeat {for (j in 1:2) i ← (i+1)+j; if (i %% 4 == 0) break};i}`

Exercise 2 Define a (higher-order) function `cycle : $\alpha^* \rightarrow \text{int} \rightarrow \alpha$` which for a given vector `v` returns a function `V ← cycle(v)` that allows to access the elements of `v` in a manner analogous to how recycling works. For instance, if `v ← c(2,5,8)` and `V ← cycle(v)`, then `V(1) ↦ 2, V(2) ↦ 5, V(3) ↦ 8, V(4) ↦ 2, V(5) ↦ 5, V(6) ↦ 8`, etc.

Exercise 3 Implement the function `rev` using loops (see the help page of `rrev` for detail on the function).

Exercise 4 Use the function `cat` to write a function `xmas` that takes an integer `n` and prints out a X-mas tree of height `n`. For instance, a simple x-mas tree of height 4 is (try placing ornaments `o` and `!` at strategic places)

```
 *
***
*****
*****
```

Exercise 5 Implement the function `strsplit : chr × chr → chr*` that takes a string `s` of characters and a separator `p` (a single character) and returns a list of maximal fragments of the string `s` that does not contain `p`. For instance, `strsplit('abc|serr|ds', '|')` \mapsto `'abc' 'serr' 'ds'`. Use only functions, `nchar` and `substr`.

Exercise 6 Write a function `flatten : chr* × chr* → log*` that takes two vectors of strings `v` and `w` and returns a Boolean vector `f` of length equal to the length of `v` such that `f[i]` is `TRUE` if and only if the string `v[i]` is present in the vector `w`. For instance, `flatten(c('a', 'b', 'c', 'd'), c('a', 'c', 'e'))` \mapsto `T F T F`.

Exercise 7 Propose vectorized version of the following procedures (without `ifelse` or any `apply` function)

```
1. function (v,w) {
  if (length(v) != length(w))
    FALSE
  else
    for (i in 1:length(v)) {
      if (v[i] != w[i]) {
        return(FALSE)
      }
    }
  TRUE
}
```

```

2. function (w,v) {
    V ← cycle(v)
    W ← cycle(w)
    n ← max(length(v),length(u))
    u ← vector()
    for (i in 1:n) {
        u[i] ← V(i) * W(i) + 2
    }
    u
}

3. function (v) {
    u ← vector()
    for (i in 1:length(v)) {
        if (i %% 2 == 1){
            u[i] ← v[i]
        } else
            u[i] ← -v[i]
        }
    u
}

4. function (v,w,u) {
    n ← max(length(v),length(w),length(u))
    x ← vector()
    V ← cycle(v)
    W ← cycle(w)
    U ← cycle(u)
    for (i in 1:n) {
        if (i %% 3 == 1) {
            x[i] ← V(i) + 2*W(i)
        } else if (i %% 3 == 2) {
            x[i] ← W(i) - U(i)
        } else {
            x[i] ← 3*U(i) + V(i) - 2*W(i)
        }
    }
    x
}

5. function (v,w) {
    n ← max(length(v),length(w))
    u ← vector()
    V ← cycle(v)
    W ← cycle(w)
    for (i in 1:n) {
        u[2*i-1] ← V(i)
        u[2*i] ← W(i)
    }
    u
}

```

```

6*. function (v) function (w) {
  if (length(v) >= length(w)) {
    v
  } else {
    n ← length(w)
    u ← vector()
    for (i in 1:n) {
      u[i] ← v[(i-1)%n+1]
    }
    u
  }
}

```

Exercise 8 Use functions from the `apply` family to propose vectorised version of the following functions

```

1. function (v,f,g) {
  u ← vector()
  for (i in 1:length(v)) {
    u[i] ← g(f(v[i]))
  }
  u
}

```

```

2. function (v,f,g) {
  l ← list()
  for (i in 1:length(v)) {
    u ← vector(length(v))
    for (j in 1:length(v)) {
      u[j] ← g(i) * f(v[j])
    }
    l[[i]] ← u
  }
  l
}

```

Exercise 9 Propose conversion functions between list and factors, vectors (matrices), and data frames.

Exercise 10* Propose a (vectorized) implementation of the built-in function `ifelse`. In particular,

```
x ← c(1,2,3,4,6,7,8,9); ifelse(x %% 2 == 0, c("E","e"), c("0","o","."))
```

should return the vector "0" "e" "." "e" "E" "." "E" "o".